
PROAUDIO® cables are conceived for any type of signal (audio/power/dmx). The excellent frequency response is due to the special insulating sheaths providing low dielectric capacitance. PROAUDIO® cables feature a high density shielding in order to eliminate buzzing and electromagnetic interferences. The outer sheathing is made of a special PVC, allowing an extremely easy handling and also grants an excellent resistance against abrasions. PROAUDIO® cables perfectly match with all kinds of audio connectors.



HC1360

Shielded balanced cable.
- O.F.C. (Oxygen Free Copper).
- Suitable for all kinds of audio signals.
- Inner conductor: tinned copper AWG20, 2x28x0.15 mm.
- Insulation: PVC diameter 1.70 mm, cotton tape with spiral cotton filler.
- Shield: tinned copper braid 8x16x0.10 mm, 92% ± 5%.
- Outer sheath: antistatic PVC ø 6.35 mm, 60 Shore.

HC1360BK **HC1360RD**
HC1360BL **HC1360GN**




Conductor D.C.R	>37 ohm/KM
Capacitance CDR/CDR	52 pF/m
Capacitance CDR/SCR	91 pF/m
Weight (Kg/mt)	0,0515
Working temperature	-30 + 70 C°



HC1380

Shielded balanced transparent cable.
- O.F.C. (Oxygen Free Copper).
- Suitable for all kinds of audio signals.
- Inner conductors: tinned copper AWG20, 2x28x0.15 mm.
- Insulation: PVC diameter 1.70 mm, cotton tape with spiral cotton filler.
- Shield: tinned copper braid 10x16x0.10 mm, 94%± 5%.
- Outer sheath: antistatic PVC ø 6.35 mm, 60 Shore.

Transparent *Trasparente* **HC1380TR**
Transparent brown *Marrone trasparente* **HC1380TB**
Transparent grey *Grigio trasparente* **HC1380TG**




Conductor D.C.R	>37 ohm/KM
Capacitance CDR/CDR	52 pF/m
Capacitance CDR/SCR	85 pF/m
Weight (Kg/mt)	0,0525
Working temperature	-30 + 70 C°



HC1340

Shielded balanced cable high-quality
- O.F.C. (Oxygen Free Copper).
- Suitable for all kinds of audio signals.
- Inner conductors: tinned copper AWG24, 2x28x0.10 mm.
- Insulation: PVC diameter 1.45 mm, cotton tape with spiral cotton filler.
- Shield: bare copper braid 6x16x0.10 mm, 90%± 5%.
- Outer jacket: antistatic PVC ø 6.35 mm, 60 Shore.

HC1340BK **HC1340RD**
HC1340BL **HC1340YL**




Conductor D.C.R	>82 ohm/KM
Capacitance CDR/CDR	73 pF/m
Capacitance CDR/SCR	125 pF/m
Weight (Kg/mt)	0,0455
Working temperature	-30 + 70 C°



HC1320

Shielded balanced high-quality cable.
- O.F.C. (Oxygen Free Copper).
- Suitable for all kinds of audio signals.
- Conductors: bare copper AWG22, 2x40X0.10 mm.
- Insulation: polyethylene, 1.45 mm diameter / CPVC: conductive PVC, 100%.
- Drain Wire: bare copper, 35x0.10 mm.
- Outer jacket: antistatic PVC ø 6.70 mm, 60 shores.

HC1320BK




Conductor D.C.R	<52 ohm/km
Capacitance CDR/CDR	62 pF/m
Capacitance CDR/SCR	98 pF/m
Weight (Kg/mt)	0,435
Working temperature	-30 + 70 C°



HC1260

High-quality shielded coaxial cable.
- O.F.C. (Oxygen Free Copper).
- Suitable for all kinds of audio signals.
- Inner conductor: bare copper AWG20, 28x0.15 mm.
- Insulation: polyethylene diameter 2.2 mm / CPVC: conductive PVC.
- Shield: tinned copper braid 8x16x0.10 mm, 100% PVC conductor, 92% ± 5%.
- Outer jacket: antistatic PVC ø 6.35 mm, 60 shores.

HC1260BK **HC1260RD**
HC1260BL **HC1260GN**




Conductor D.C.R	<37 ohm/KM
Capacitance CDR/CDR	52 pF/m
Capacitance CDR/SCR	85 pF/m
Weight (Kg/mt)	0,046
Working temperature	-30 + 70 C°



HC1345

Shielded balanced cable, external sheath with a reduced diameter for permanent installations.
- O.F.C. (Oxygen Free Copper).
- Suitable for all kinds of audio signals.
- Inner conductors: tinned copper AWG20, 2x12x0.15 mm.
- Insulation: PVC diameter 1.10 mm / CPVC: conductive PVC.
- Shield: tinned copper braid 80x0.10 mm, 90% ± 5%.
- Outer jacket: antistatic PVC ø 3.5 mm, 60 shores.

HC1345GR




Conductor D.C.R	200 ±10% ohm/KM
Capacitance CDR/CDR	170 pF/m
Capacitance CDR/SCR	310 pF/m
Weight (Kg/mt)	0,016
Working temperature	-30 + 80 C°



HC1240

High-quality shielded coaxial cable.
- O.F.C. (Oxygen Free Copper).
- Suitable for all kinds of audio signals.
- Conductor: tinned copper AWG20, 28x0.15 mm.
- Insulation: polyethylene diameter 1.70 mm / CPVC: conductive PVC.
- Shield: bare copper braid 5x16x0.10 mm, 90%± 5%.
- Outer jacket: antistatic PVC ø 6.35 mm, 60 shores.

HC1240BK **HC1240RD**
HC1240BL **HC1240YL**



Conductor D.C.R	<64 ohm/KM
Capacitance CDR/CDR	135 pF/m
Weight (Kg/mt)	0,0445
Working temperature	-30 + 70 C°