PBC63614

63 A 60x40x54 cm



Power distribution box, 63A 5p input plug

Structure:
- IP 54 shock resistant, robust and mobile insulated thermoplastic box with stackable shape
- IP 55 hinged windows to protect switches and instruments
- Box dimensions (WxHxD): 60x40x54 cm

Input:
- 63A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP67, 1pc (code 913315)

Output:
- 32A-5p (3P+N+E) panel mount CEE socket with slim flange, 400V 50/60Hz IP44, 1pc (code 912425)
- 16A-3p (1P+N+E) panel mount CEE socket, 230V 50/60Hz IP44, 6pcs (code 911413)
- Panel mount multipin sockets 19P IP67 Socapex, 4pcs (code 916141)

Protection:
- 4P magneto-thermic switch, 4 modules, 63A/6kA, 1pc (code 923121)
- Residual current circuit breaker overcurrent protection, 4P, 4 mod, 40A, 30mA, 5pcs cod.(923322)
- Residual current circuit breaker w overcurrent protection, 4P, 4 mod,32A,6kA,30mA, 1pc
- Magneto-thermic switch 1P+N, 1 module, 16A/4.5kA, 30pcs (code 921111)

Tools:
- 4P fuser block, 4 modules, 1pc (code 927114)
- Digital multimeter, 3 voltmeters (35-480), 3 ammeters (5-8000A), timer, 4 modules, 1pcs (code 927531)

PBC63123

63 A 60x40x54 cm



Power distribution box, 63A 5p input plug

Structure:
- IP 54 shock resistant, robust and mobile insulated thermoplastic box with stackable shape
- IP 55 hinged windows to protect switches and instruments
- Box dimensions (WxHxD): 60x40x54 cm

Input:
- 63A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP67, 1pc (code 913315)

Output:
- 32A-5p (3P+N+E) panel mount CEE socket with slim flange, 400V 50/60Hz IP44, 3pcs (code 912425)
- 16A-3p (1P+N+E) panel mount CEE socket, 230V 50/60Hz IP44, 12pcs (code 911413)

Protection:
- 4P magneto-thermic switch, 4 modules, 63A/6kA, 1pc (code 923121)
- Residual current circuit breaker overcurrent protection, 4P, 4 mod, 40A, 30mA, 2pcs(923322)
- Residual current circuit breaker w overcurrent protection, 4P, 4 mod,32A,6kA,30mA, 3pcs
- Magneto-thermic switch 1P+N, 1 module, 16A/4.5kA, 12pcs (code 921111)

Tools:
- 4P fuser block, 4 modules, 1pc (code 927114)
- Digital multimeter, 3 voltmeters (35-480), 3 ammeters (5-8000A), timer, 4 modules, 1pc (code 927531)

PBC3210

32 A 40x34x35 cm



Portable Power distribution box, 32A 5p input plug

Structure:
- IP54 shock resistant, robust and mobile insulated thermoplastic box with stackable shape
- IP55 hinged windows to protect switches and instruments
- Box dimensions (WxHxD): 40x34x35 cm

Input:
- 32A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP44, 1pc (code 912315)

Output:
- 16A-3p (1P+N+E) panel mount CEE socket, 230V 50/60Hz IP44, 6pcs (code 911413)
- 32A-5p (3P+N+E) panel mount CEE socket with slim flange, 400V 50/60Hz IP44, 1pc (code 912425)

Protection:
- Residual current circuit breaker w overcurrent protection, 4P, 7 modules, 32A, 10kA, 30mA, 1pc (code 922432)
- 4P magneto-thermic switch , 4 modules, 32A/6kA, 1pc (code 922122)
- 2P magneto-thermic switch 1P+N, 1 module, 16A/4.5kA, 6pcs (code 921111)

Tools:
- Digital voltmeter, tension range 35-480V, 4 modules, 1pc (code 927511)
- Voltmeter commutator for DIN bar, 7 position, 3 modules, 1pc (code 927411)
- 4P fuser block, 4 modules, 1pc (code 927114)

PBL6365

63 A 32x32x32 cm



Portable Power distribution box, 63A 5p input plug

Structure:
- IP54 shock resistant, robust and mobile insulated thermoplastic box
- Box dimensions (WxHxD): 32x32x32 cm

Input:
- 63A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP67, 1pc (code 913315)

Output:
- 32A-5p (3P+N+E) panel mount CEE socket, 400V 50/60Hz IP67, 2pcs (code 912415)

Protection:
- Residual current circuit breaker w overcurrent protection, 4P, 7 mod, 63A, 10kA, 30mA, 1pc
- Magneto-thermic switch (1P+N), 2 modules, 32A/6kA, 2pcs

Tools:
- 4P fuser block, 4 modules, 1pc
- Triple LED indicator, 1 module, colour red, 1pc

PBL6376

63 A 32x32x32 cm



Portable Power distribution box, 63A 5p input plug

Structure:
- IP54 shock resistant, robust and mobile insulated thermoplastic box
- Box dimensions (WxHxD): 32x32x32 cm

Input:
- 63A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP67, 1pc (code 913315)

Output:
- 32A-3p (1P+N+E) panel mount CEE socket withslim flange, 230V 50/60Hz IP44, 6pcs (code 912423)

Protection:
- Residual current circuit breaker w/ overcurrent protection, 4P, 7 mod, 63A, 10kA, 30mA, 1pc
- Magneto-thermic switch (1P+N), 2 modules, 32A/6kA, 6pcs

Tools:
- 4P fuser block, 4 modules, 1pc
- Triple LED indicator, 1 module, colour red, 1pc

PBL3221

32 A 32x32x32 cm



Portable Power distribution box, 32A 5p input plug

Structure:
- IP54 shock resistant, robust and mobile insulated thermoplastic box
- Box dimensions (WxHxD): 32x32x32 cm

Input:
- 32A-5p (3P+N+E) panel mount CEE plug, 400V 50/60Hz IP44, 1pc (code 912315)

Output:
- 16A-3p (1P+N+E) panel mount CEE socket, 230V 50/60Hz IP44, 3pcs (code 911413)
- 32A-5p (3P+N+E) panel mount CEE socket with slim flange, 400V 50/60Hz IP44, 1pc (code 912425)

Protection:
- Residual current circuit breaker w overcurrent protection, 4P, 7 modules, 32A, 10kA, 30mA, 1pc
- 4P magneto-thermic switch , 4 modules, 32A/6kA, 1pc
- Magneto-thermic switch (1P+N), 2 modules, 16A/4,5kA, 3pcs

Tools:
- 4P fuser block, 4 modules, 1pc
- Triple LED indicator, 1 module, colour red, 1pc