



MA615A

Wide-dispersion active module for line-array, 1500W D-class amplifier, 2-way, 137dB SP

- Low frequency: 2x10'' neodymium woofer/2.6''v.c.
- High frequency: 1.4'' neodymium driver/3''v.c.
- Frequency response: 65-18000 Hz (±3dB)
- Coverage angle HxV: 100x30°
- Hi-definition system for reproduction of voice and music in live and recorded performance
- For sound installations in environments requiring dynamics and high sound pressure
- Birch plywood enclosure
- DSP with 4 presets (1-3/4-6 unit - full range/ high pass filter) for selection of optimal frequency response

MA615P

Wide-dispersion passive module for line-array, 2-way 500W AES, 137dB SPL

- Low frequency: 2x10'' neodymium woofer/2.6''v.c.
- High frequency: 1.4'' neodymium driver/3''v.c.
- Frequency response: 65-18000 Hz (±3dB)
- Coverage angle HxV: 100x30°
- Hi-definition system for reproduction of voice and music in live and recorded performance
- For sound installations in environments requiring dynamics and high sound pressure
- Birch plywood enclosure

MA615



2x10" Nd



1,4" Nd



DIGITAL AMP*



DSP*



RIGGING



100°x30°



DEDICATED PRESET**

MA615A TECHNICAL DATA

LOUDSPEAKERS

- System type: active 2 way

COMPONENTS

- Low frequency: 10" neodymium woofer / 2.6" v.c.
- High frequency: 1.4" neodymium driver / 3" v.c.

FEATURES

- Built-in amp LF/HF: 1500W
- SPL max: 137dB @1m (free field)

ACOUSTICAL SPECIFICATIONS

- SPL cont/peak: 131/137dB @1m (free field)
- Frequency response: 65-18000Hz (±3dB)
- Coverage angle HxV: 100x30°
- Cross over frequency: 1100Hz

ELECTRONICS

- Amplifier: 1500 digital
- Input sensitivity: 4 dBu (1,228Vrms) adjustable
- Protection: RMS limiter, fast limiter, temp.
- User controls: 1-3/4-6 unit - full range/ high pass filter
- Processor: DSP
- Operating voltage/frequency: 220 V ±10%, 50 Hz

INPUT/OUTPUT CONNECTORS

- Input signal: Neutrik XLR IN/OUT
- Power connection: powerCON IN/OUT

CABINET CONSTRUCTION

- Cabinet material: 18mm birchplywood
- Sospension system: fixed angle bracket, M8 eyebolt, 35 mm pole mount
- Angle: 15° trapezoidal taper
- Handles: 2 on side

PHYSICAL

- Dimensions (WxHxD): 656x364x497mm
- Weight: 30kg

MA615P TECHNICAL DATA

LOUDSPEAKERS

- System type: passive 2 way

COMPONENTS

- Low frequency: 10" neodymium woofer / 2.6" v.c.
- High frequency: 1.4" neodymium driver / 3" v.c.

FEATURES

- AES/program power: 500/1000W
- SPL max: 137dB @1m (free field)

ACOUSTICAL SPECIFICATIONS

- Sensitivity: 100dB @1W/1m (free field)
- Impedance: 8 Ohm
- SPL cont/peak: 131/137dB @1m (free field)
- Frequency response: 70-18000Hz (±3dB)
- Coverage angle HxV: 100x30°
- Cross over frequency: 1100Hz
- Protection: H.F. signal compression

INPUT/OUTPUT CONNECTORS

- Input signal: Neutrik NL4 IN/OUT

CABINET CONSTRUCTION

- Cabinet material: 18mm birchplywood
- Sospension system: fixed angle bracket, M8 eyebolt, 35 mm pole mount
- Angle: 15° trapezoidal taper
- Handles: 2 on side

PHYSICAL

- Dimensions (WxHxD): 656x364x497mm
- Weight: 28kg

*active version only

**passive version only



MA605A

High-directivity active module for line-array, 1500W D-class amplifier, 2-way, 138dB SPL

- Low frequency: 2x10" neodymium woofer/2.6"v.c.
- High frequency: 1.4" neodymium driver/3"v.c.
- Frequency response: 65-18000 Hz (±3dB)
- Coverage angle HxV: 80x10°
- Hi-definition system for reproduction of voice and music in live and recorded performance
- For sound installations in environments requiring dynamics and high sound pressure
- Birch plywood enclosure
- DSP with 4 presets (1-3/4-6 unit - full range/ high pass filter) for selection of optimal frequency response

MA605P

High-directivity passive module for line-array, 2-way 500W AES, 138dB SPL

- Low frequency: 2x" neodymium woofer/2.6"v.c.
- High frequency: 1.4" neodymium driver/3"v.c.
- Frequency response: 65-18000 Hz (±3dB)
- Coverage angle HxV: 80x10°
- Hi-definition system for reproduction of voice and music in live and recorded performance
- For sound installations in environments requiring dynamics and high sound pressure
- Birch plywood enclosure

MA605



2x10" Nd



1,4" Nd



DIGITAL AMP*



DSP*



RIGGING



80°x10°



DEDICATED PRESET**

MA605A TECHNICAL DATA

LOUDSPEAKERS

- System type: active 2 way

COMPONENTS

- Low frequency: 10" neodymium woofer / 2.6" v.c.
- High frequency: 1.4" neodymium driver / 3" v.c.

FEATURES

- Built-in amp LF/HF: 1500W
- SPL max: 138dB @1m (free field)

ACOUSTICAL SPECIFICATIONS

- SPL cont/peak: 132/138dB @1m (free field)
- Frequency response: 65-18000Hz (±3dB)
- Coverage angle HxV: 80x10°
- Cross over frequency: 1100Hz

ELECTRONICS

- Amplifier: 1500 digital
- Input sensitivity: 4 dBu (1,228Vrms) adjustable
- Protection: RMS limiter, fast limiter, temp.
- User controls: 1-3/4-6 unit - full range/ high pass filter
- Processor: DSP
- Operating voltage/frequency: 220 V ±10%, 50 Hz

INPUT/OUTPUT CONNECTORS

- Input signal: Neutrik XLR IN/OUT
- Power connection: powerCON IN/OUT

CABINET CONSTRUCTION

- Cabinet material: 18mm birchplywood
- Sospension system: fixed angle bracket, M8 eyebolt, 35 mm pole mount
- Angle: 5° trapezoidal taper
- Handles: 2 on side

PHYSICAL

- Dimensions (WxHxD): 656x332x497mm
- Weight: 30kg

MA605P TECHNICAL DATA

LOUDSPEAKERS

- System type: passive 2 way

COMPONENTS

- Low frequency: 10" neodymium woofer / 2.6" v.c.
- High frequency: 1.4" neodymium driver / 3" v.c.

FEATURES

- AES/program power: 500/1000W
- SPL max: 138dB @1m (free field)

ACOUSTICAL SPECIFICATIONS

- Sensitivity: 101dB @1W/1m (free field)
- Impedance: 8 Ohm
- SPL cont/peak: 132/138dB @1m (free field)
- Frequency response: 70-18000Hz (±3dB)
- Coverage angle HxV: 80x10°
- Cross over frequency: 1100Hz
- Protection: H.F. signal compression

INPUT/OUTPUT CONNECTORS

- Input signal: Neutrik NL4 IN/OUT

CABINET CONSTRUCTION

- Cabinet material: 18mm birchplywood
- Sospension system: fixed angle bracket, M8 eyebolt, 35 mm pole mount
- Angle: 5° trapezoidal taper
- Handles: 2 on side

PHYSICAL

- Dimensions (WxHxD): 656x332x497mm
- Weight: 28kg

*active version only

**passive version only