


HC5340

DMX cable with constant impedance, 2 twisted poles, external sheath with reduced diameter.
- O.F.C. (Oxygen Free Copper).
- Specific for the connection of devices using DMX512 protocol featuring a 120 Ohm nominal impedance.
- Inner conductor: tinned copper AWG24, 2x7x0.20 mm.
- Insulation: polyethene 1.35 mm diameter, foil tape with spiral cotton filler.
- Shield: tinned copper 6x16x0.10 mm, 90%± 5%.
- Outer jacket: PVC diameter 5.40 mm, 60 Shore.

HC5340BK **HC5340GR**

Impedance	110 ±7% Ohm/m
100MHz line loss	10,5 MHz db/100
Capacitance CDR/CDR	42 pF/m
Capacitance CDR/SCR	75 pF/m
Weight (Kg/mt)	0,098
Working temperature	-30 + 60 C°







HC5640

DMX cable, two couples, constant impedance, 2 pairs of twisted poles, external sheath with a reduced diameter.
- O.F.C. (Oxygen Free Copper).
- Specific for the connection of devices using DMX512 protocol featuring a 120 Ohm nominal impedance.
- Inner conductor: tinned copper AWG24, 2x7x0.20 mm.
- Insulation: polyethene 1.35 mm diameter, foil tape with spiral cotton filler.
- Shield: tinned copper 6x16x0.10 mm, 90%± 5%.
- Outer jacket: PVC diameter 7.60 mm, 60 shores.

HC5640BK

Impedance	110 ±7% Ohm/m
100MHz line loss	10,5 MHz db/100
Capacitance CDR/CDR	42 pF/m
Capacitance CDR/SCR	75 pF/m
Weight (Kg/mt)	0,098
Working temperature	-30 + 60 C°






HC6640 - HIGH PERFORMANCE CABLE MADE IN ITALY


HC6640

Balanced power supply/audio cable.
- O.F.C. (Oxygen Free Copper)
- Power conductors: bare copper CU 0,245, AWG13
- Power insulation: PVC, 3.6 mm Ø
- Signal conductors: bare copper AWG 22, 11x0,20mm
- Signal insulation: polyethene, 1.45 mm Ø / CPVC: conductive PVC
- Inner jacket: PVC, Ø 4,5 mm
- Outer jacket: PVC, Ø 9.8 mm
- Colour: black, grey
- Dimensions: 3x1.5+2x0.35 mmq
- Weight: 210 kg/km
- Working temperature: -30/60°C

HC6640BK **HC6640GR**

Features signal conductors	
Conductor D.C.R	<55 ohm/KM
Capacitance CDR/CDR	62 pF/m
Capacitance CDR/SCR	93 pF/m
Features Power conductors	
Conductors section	3 x 1,50
Conductor D.C.R.	21 ± 5% Ohm/Km
Weight (Kg/mt)	0,0525
Working temperature	-30 + 60 C°





HC7640 - HIGH PERFORMANCE CABLE MADE IN ITALY

HC7640

Balanced power supply/DMX 120 Ohm.
- O.F.C. (Oxygen Free Copper)
- Power conductors: bare copper AWG24, 2x7x0.20mm
- Power insulation: PVC, 3 mm Ø
- Signal conductors: bare copper AWG 24, 7x0,20
- Signal insulation: polyethene, 1.35 mm Ø / CPVC: conductive PVC
- Inner jacket: PVC, Ø 4,5 mm
- Outer jacket: PVC, Ø 10.30 mm
- Colour: black, grey
- Dimensions: 3x1.5+2x0.22 mmq
- Weight: 210 kg/km
- Working temperature: -30/60°C

HC7640BK **HC7640GR**

Features signal conductors	
100MHz line loss	10,5 MHz db/100
Capacitance CDR/CDR	42 pF/m
Capacitance CDR/SCR	75 pF/m
Features Power conductors	
Conductors section	3 x 1,50
Conductor D.C.R.	21 ± 5% Ohm/Km
Weight (Kg/mt)	0,0525
Working temperature	-30 + 60 C°

