



HD100T

2-way horn coaxial speaker with 6.5" LF driver and 1.5" HF driver, compact size and high acoustic performance.

LOUDSPEAKERS

- System type: coaxial horn loaded

COMPONENTS

- Low frequency: 6.5"
- High frequency: 1"

FEATURES

- AES/program power: 50/100W
- Input 100 V: 2.6/4.5/9/12.5/25/50W

ACOUSTICAL SPECIFICATIONS

- Sensitivity: 86dB @1W/1m (free field)
- Impedance: Low impedance 8 Ohm
- Constant voltage: 70/100 V
- Frequency response: 250÷10000Hz (±3dB)

INPUT/OUTPUT CONNECTORS

- Input signal: terminal with wire

PHYSICAL

- IP rating: 65
- Dimensions (WxHxD): 362x252x310mm
- Weight: 4kg



GS63T

Outdoor speaker, ideal for background music reproduction.

LOUDSPEAKERS

- System type: garden speaker

COMPONENTS

- Low frequency: 6.5"
- High frequency: 1"

FEATURES

- AES/program power: 25/50W
- Input 100 V: 12.5/25W

ACOUSTICAL SPECIFICATIONS

- Sensitivity: 94dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 130÷15.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS

- Input signal: terminal with wire

PHYSICAL

- IP rating: 55
- Weight: 3.45kg



GS62T

Outdoor speaker, ideal for background music reproduction.

LOUDSPEAKERS

- System type: garden speaker

COMPONENTS

- Low frequency: 6"
- High frequency: 1"

FEATURES

- AES/program power: 20/40W
- Input 100 V: 10/20W

ACOUSTICAL SPECIFICATIONS

- Sensitivity: 94dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 130÷15.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS

- Input signal: terminal with wire

PHYSICAL

- IP rating: 55
- Weight: 2.8kg



GR63T

Outdoor applications speaker, ideal for background music reproduction.

LOUDSPEAKERS

- System type: garden speaker

COMPONENTS

- Low frequency: 6"
- High frequency: 1"

FEATURES

- AES/program power: 30/60W
- Input 100 V: 30W

ACOUSTICAL SPECIFICATIONS

- Sensitivity: 91dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 80÷15.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS

- Input signal: terminal with wire

PHYSICAL

- IP rating: 44
- Dimensions (WxHxD): 400x300x280mm
- Weight: 6kg



GR62T

Outdoor applications speaker, ideal for background music reproduction.

LOUDSPEAKERS

- System type: garden speaker

COMPONENTS

- Low frequency: 5"
- High frequency: 1"

FEATURES

- AES/program power: 20/40W
- Input 100 V: 10/20W

ACOUSTICAL SPECIFICATIONS

- Sensitivity: 89dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 100÷15.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS

- Input signal: terminal with wire

PHYSICAL

- IP rating: 44
- Dimensions (WxHxD): 230x210x270mm
- Weight: 3.5kg



AT120

Line attenuator for constant voltage systems.

- Volume control: 4 positions + OFF.



AT60

Line attenuator for constant voltage systems.

- Volume control: 4 positions + OFF.



WP1

Remote control panel for MZX84 and MZA8412. It allows to control the zone volume locally and enter local sources.

- Inputs: 1 micro XLR - 1 line with 2 x RCA
- CAT5 / RJ45 connection
- Dimensions 80x80x50
- Weight 0.5 kg