
SU22

Aluminium extruded tubes, Ø 35X2 mm 6082 T6

- Plate: conical quick-lock connectors
- Fast connection kit FCU3 included




Variants

Code	Tube (mm)	Diagonal (mm)	W (cm)	H (cm)	D (cm)	Weight (kg)	Volume (mc)
SU22050	35x1.5	8	50	3.5	3.5	0.35	0.000
SU22100	35x1.5	8	100	3.5	3.5	0.70	0.001
SU22150	35x1.5	8	150	3.5	3.5	1.05	0.001
SU22200	35x1.5	8	200	3.5	3.5	1.40	0.002
SU22250	35x1.5	8	250	3.5	3.5	1.75	0.002
SU22300	35x1.5	8	300	3.5	3.5	2.10	0.003

Joints

Variants

Code	Type	Way (nr)	Angle	Orient.	Vertex	W (cm)	H (cm)	D (cm)
SU22L2045	L2	2	45°	-	-	50	3.5	50
SU22L2060	L2	2	60°	-	-	50	3.5	50
SU22L2090	L2	2	90°	-	-	50	3.5	50
SU22L2120	L2	2	120°	-	-	50	3.5	50
SU22L2135	L2	2	135°	-	-	50	3.5	50
SU22T3	T3	3	90°	-	-	50	3.5	50



SU22L2045

2-way corner for SU22, extrude tube 35x2mm, FCU3 included



SU22T3

3-way joint for SU22 Series, extrude tube 35x2mm, x2 FCU3 included



Included

FCU3


Quick connection, 1 spigot, 2 pins, 2 safety spring, SU22

LF5H

4-way H joint for LITEFRAME series

- Extruded tubes: Ø 48.3 mm
- Plate: conical quick-lock connectors
- 4 pin with self-locking nuts included
- Material: aluminium 6082-T6
- Available finish: aluminium, black
- FCPLN safety pins included (x4)





Variants


Code	Dimensions (mm)	Finish	Weight (kg)
LF5H1075AL	1000X750	Aluminium	2.22
LF5H1075BK	1000X750	Black	2.22
LF5H4175AL	415x750	Aluminium	3.45
LF5H4175BK	415x750	Black	3.45

LF5X

2-way T joint for LITEFRAME series

- Extruded tubes: Ø 48.3 mm
- Plate: conical quick-lock connectors
- 2 pin with self-locking nuts included
- Material: aluminium 6082-T6
- SWL (Safe working load): 100 kg
- Available finish: aluminium, black
- FCPLN safety pins included (x2)





Variants

Code	Dimensions (mm)	Finish	Weight (kg)
LF5X5046AL	500x460	Aluminium	1.28
LF5X5046BK	500x460	Black	128