

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 8x8W RGBW/FC LFDs.
- Luminous flux: @full 2268lm
- Lux: 15° @full 28431lux @3m

OPTICS

- Beam angle: 15°
- Additional optics: 25° / 45° (optional)

COLOUR SYSTEM

- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets

CONTROL

- Protocols: DMX512
- DMX channels: 4 / 6 / 10 channel

ELECTRONICS

• Dimmer: linear 0~100% electronic dimmer

- Dimmer curves: 4 different dimming curves available
- Strobe / shutter: 1 30 Hz. electronic

FI FCTRICAL

- Power consumption (at 230V): 55W
- Output (at 230V): 24 units on a single power line

PHYSICAL

- Adaptors: XLR and 16A adaptors included
- Signal connection: IP connectors
- Power connection: IP connector
- IP rating: 65
- Dimensions (WxHxD): 316x235x81mm
- Weight: 5.16kg

ARCPOD8

8 x 8W outdoor compact wash light











8x8W RGBW/FC LFDs

(25°-45° optional)

DMX512

65 for temporary outdoor application, not for fixed installation

ARCPOD8 is a wash light with 8x8W RGBW/FC LED source designed for outdoor installations where a high-performance projector with superior brightness and chromatic precision is required. The rectangular shape design and the super-slim profile allows the ARCPOD8 to be easily integrated into any architectonic installation or setting whilst also being functional in outdoor (IP 65) environments due to the construction of chassis in die-cast aluminium and tempered glass with no ventilation fans. ARCPOD8 is a compact projector capable of lighting large spaces both as a stage wash in temporary events and for projects of architectural lighting

FEATURES

- 4D (RGBW) colour mixing
- DMX virtual colour wheel
- CTC
- Low 55W power consumption and LED source expected life of over 50000 hours
- User menu and settings are accessed through a 4 button touch-sensitive LED interface while 3 different DMX modes (4-10 channel) available



TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 12x8W RGBW/FC LFDs
- Luminous flux: @full 3177lm
- Lux: 15° @full 4020lux @3m

OPTICS

- Beam angle: 15°
- Additional optics: 25° 45° (optional)

COLOUR SYSTEM

- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets

CONTROL

- Protocols: DMX512
- DMX channels: 4 / 6 / 10 / 24 / 29channel
- Pixel control: pixel2pixel control

FLECTRONICS

• Dimmer: linear 0~100% electronic dimmer

- Dimmer curves: 4 different dimming curves available
- Strobe / shutter: 1 30 Hz. electronic

FI FCTRICAL

- Power consumption (at 230V): 103W
- Output (at 230V): 16 units on a single power line

PHYSICAL

- Adaptors: XLR and 16A adaptors included
- Signal connection: IP connectors
- Power connection: IP connector
- IP rating: 65
- Dimensions (WxHxD): 990x200x188mm
- Weight: 8.7kg

ARCSHINE12

12 x 8W outdoor compact linear wall wash light











12x8W RGBW/FC LFDs

(25°-45° optional)

DMX512

65 for temporary outdoor application, not for fixed installation

ARCSHINE12 is a linear wall washer with 12x8W RGBW/FC LED source designed for outdoor installations where a high-performance projector with superb brightness and chromatic precision is required. The linear shape design and the super-slim profile allows the ARCSHINE12 to be easily integrated into any architectonic design both indoor and outdoor (IP 65) due to the construction of chassis in die-cast aluminium and tempered glass with ventilation fans. ARCSHINE12 is a compact projector capable of lighting large spaces both as a stage wash in temporary events and for architectural lighting projects

FFATURES

- 4D (RGBW) colour mixing
- DMX virtual colour wheel
- CTC
- Low 103W power consumption and LED source expected life of over 50000 hours
- User menu and settings are accessed through a 4 button touch-sensitive LED interface while 5 different DMX modes (4-53 channel) available