



ARCPD21

21 x 8W outdoor compact wash light



LIGHT SOURCE

21x8W
RGBW/FC LEDs



BEAM ANGLE

15°
(25°-45° optional)



CONNECTIVITY

DMX512



IP RATING

65 for temporary
outdoor
application, not for
fixed installation

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 21x8W RGBW/FC LEDs
- Luminous flux: @full 2763lm
- Lux: 15° @full 7493lux @3m

OPTICS

- Beam angle: 15°
- Additional optics: 25° / 45° (optional)

COLOUR SYSTEM

- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets

CONTROL

- Protocols: DMX512
- DMX channels: 4 / 6 / 10channel

ELECTRONICS

- Dimmer: linear 0~100% electronic dimmer
- Dimmer curves: 4 different

dimming curves available

- Strobe / shutter: 1 - 30 Hz, electronic

ELECTRICAL

- Power consumption (at 230V): 144W
- Output (at 230V): 10 units on a single power line

PHYSICAL

- Adaptors: XLR and 16A adaptors included
- Signal connection: IP connectors
- Power connection: IP connector
- IP rating: 65
- Dimensions (WxHxD): 472x299x98mm
- Weight: 9.18kg

FEATURES

- 4D (RGBW) colour mixing
- DMX virtual colour wheel
- CTC
- Low 144W power consumption and LED source expected life of over 50000 hours
- User menu and settings are accessed through a 4 button touch-sensitive LED interface while 3 different DMX modes (4-10 channel) available.



ARCPD8

8 x 8W outdoor compact wash light



LIGHT SOURCE

8x8W
RGBW/FC LEDs



BEAM ANGLE

15°
(25°-45° optional)



CONNECTIVITY

DMX512



IP RATING

65 for temporary
outdoor
application, not for
fixed installation

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 8x8W RGBW/FC LEDs
- Luminous flux: @full 2268lm
- Lux: 15° @full 28431lux @3m

OPTICS

- Beam angle: 15°
- Additional optics: 25° / 45° (optional)

COLOUR SYSTEM

- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets

CONTROL

- Protocols: DMX512
- DMX channels: 4 / 6 / 10channel

ELECTRONICS

- Dimmer: linear 0~100% electronic dimmer

- Dimmer curves: 4 different dimming curves available
- Strobe / shutter: 1 - 30 Hz, electronic

ELECTRICAL

- Power consumption (at 230V): 55W
- Output (at 230V): 24 units on a single power line

PHYSICAL

- Adaptors: XLR and 16A adaptors included
- Signal connection: IP connectors
- Power connection: IP connector
- IP rating: 65
- Dimensions (WxHxD): 316x235x81mm
- Weight: 5.16kg

FEATURES

- 4D (RGBW) colour mixing
- DMX virtual colour wheel
- CTC
- Low 55W power consumption and LED source expected life of over 50000 hours
- User menu and settings are accessed through a 4 button touch-sensitive LED interface while 3 different DMX modes (4-10 channel) available