



LUMIPAR12IP

- Source: 12x9W RGBW LEDs
- Luminous flux: (D20) 3900 lm (D45) 6700lm
- Beam angle: Available in 20° or 45°
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 4/6/11channel
- Power consumption (at 230V): 110W
- Output (at 230V): 33 units on a single power line
- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Power connection: Seetronic powerKon waterproof IN/OUT connectors
- IP rating: 65 for outdoor events
- Dimensions (WxHxD): 305x326x177mm
- Weight: 6.2kg

Variants

LUMIPAR12IP20D

Beam Angle: 20°

LUMIPAR12IP45D

Beam Angle: 45°



LUMIPAR7IP

- Source: 7x9W RGBW LEDs
- Luminous flux: (D20) 2945 lm (D45) 3835lm
- Beam angle: Available in 20° or 45°
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 4/6/11channel
- Power consumption (at 230V): 65W
- Output (at 230V): 58 units on a single power line
- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Power connection: Seetronic powerKon waterproof IN/OUT connectors
- IP rating: 65 for outdoor events
- Dimensions (WxHxD): 240x286x154mm
- Weight: 3.64kg

Variants

LUMIPAR7IP20D

Beam Angle: 20°

LUMIPAR7IP45D

Beam Angle: 45°



VERSAPAR

- Source: 12x10W RGBW LEDs
- Luminous flux: (10°) 1223 - (60°) 1423lm
- Zoom: 10-60° motorised linear zoom
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 5/7/10channel
- Power consumption (at 230V): 121W
- Output (at 230V): 12 units on a single power line
- Signal connection: XLR 3p+5p IN/OUT connectors
- Power connection: Neutrik powerCON IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 262x350x261mm
- Weight: 5.5kg



WIFI USB
(optional)

MINIVERSAPAR

- Source: 7x10W RGBW LEDs
- Luminous flux: (10°) 1012lm (40°) 1335lm
- Lux: (10°) 4415 lux, (40°) 378lux @3m
- Zoom: 10°- 40° motorised linear zoom
- Lens type: honeycomb gapless plano-convex optics
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 5/7/10channel
- Dimmer: linear 0~ 100% electronic dimmer
- Dimmer curves: different dimming curves available
- Strobe / shutter: 1/28 Hz, electronic
- Power consumption (at 230V): 69,2W
- Output (at 230V): 54 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p+5p IN/OUT connectors
- Power connection: Seetronic powerKon IN/OUT connectors
- IP rating: 30 with a protective vent to prevent condensation, dust, compensate pressure
- Dimensions (WxHxD): 235x156x301mm
- Weight: 3.7kg



WIFIUSB
(optional) LUMIPARIRCH
(optional)

LUMIPAR12UH

- Source: 12x8W RGBWAP LEDs
- Luminous flux: 2537lm
- Beam angle: 25°
- Colour mixing: RGBWAP/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 6/11channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 83W
- Output (at 230V): 30 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: variants available
- IP rating: 44
- Dimensions (WxHxD): 253x200x237mm
- Weight: 3.3kg

Variants

LUMIPAR12UH3

Power connections: IEC 3p IN/OUT

LUMIPAR12UH3P

Power connections: powerCON 3p



WIFIUSB
(optional) LUMIPARIRCH
(optional)

LUMIPAR12UQPRO

- Source: 12x8W RGBW LEDs
- CT: W: 6600K
- Luminous flux: 3035.7lm
- Beam angle: 16°
- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets
- Protocols: DMX512
- DMX channels: 4/9channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 77W
- Output (at 230V): 17 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: variants available
- Power connection: variants available
- IP rating: 44
- Dimensions (WxHxD): 253x200x237mm
- Weight: 3.3kg

Variants

LUMIPAR12UQPRO3

Signal connections: IEC 3p IN/OUT

LUMIPAR12UQPRO5

Signal connections: powerCON 5p IN/OUT

