



## DIGISTRIP40

DIGISTRIP40 is a LED video strip for the rental market with 25 mm pixel pitch and an extensive range of optical accessories for a wide variety of looks (black and white included, transparent on demand). The external control unit DIGIDRIVER is compatible with Art-Net and Kling-Net protocol and runs both signal and power over a 4 poles cable that provides greater stability and connection in a daisy chain (up to 24 DIGISTRIP).

- Source: 40x0.25W SMD5050 RGB LEDs
- Colour mixing: RGB/FC
- Protocols: Art-Net, Kling-Net
- Pixel control: pixel2pixel control
- Power consumption (at 230V): 26,7W
- Output (at 230V): 24 units on a single DIGIDRIVER line
- Signal connection: XLR 4p IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 1000x37x117mm
- Weight: 2.2kg

\*DIGIDRIVER required



## DIGITUBE

DIGITUBE is an evolution in the range of pixel effects, adding the 3rd dimension to the creation of visual shows through its tubular shapes and capacity to project at 360°. Each tube is equipped with 2 lines of 40 RGB/FC LED with individual pixel control, 1 m long. Its modular design allows DIGITUBE to be mounted and configured with maximum flexibility, such as suspended below the ceiling to create 3D effects on XYZ axes.

- Source: 80x0.25W SMD5050 RGB LEDs
- Colour mixing: RGB/FC
- Protocols: Art-Net, Kling-Net
- Pixel control: pixel2pixel control
- Power consumption (at 230V): 29,3W
- Output (at 230V): 16 units on a single DIGIDRIVER line
- Signal connection: Seetronic XLR 4p IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 1155x28mm
- Weight: 0.33kg

\*DIGIDRIVER required





WIFIUSB (optional)  
LUMIPARIRCH (optional)

## POLAR700

POLAR700 is a revolutionary LED strobe, engineered to offer a true explosion of light and a range of dynamic effects - all in a unique fixture. POLAR700 can be also controlled wirelessly through the optional USB WIFI transceiver in combination with WIFIBOX and the SmartColors app.

- Source: 180x0,5W cold white LEDs
- CT: 6000K
- CRI: 72
- Luminous flux: 3506lm
- Beam angle: 110°
- Protocols: DMX512
- DMX channels: 2/5/8channel
- Pixel control: section control
- W-DMX: optional, proprietary protocol compatible with WIFIBOX, WDBOX
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 43.1W
- Output (at 230V): 30 units on a single power line
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 233x114x167mm
- Weight: 1.6kg



LUMIPARIRCH (optional)

## POLAR500

POLAR500 is a LED strobe engineered to offer a true explosion of light and a range of dynamic effects - all in a unique fixture. The light source is composed of 90 SMD 6500°K 0,5W LED allowing for a full-on continuous operation and capable to offer an equal output of conventional 500W strobe from just one-sixth of the nominal power.

- Source: 90x0,5W cold white LEDs
- CT: 6000K
- CRI: 72
- Luminous flux: 1808lm
- Beam angle: 110°
- Protocols: DMX512
- DMX channels: 1/4/5/8channel
- Pixel control: ring control
- Power consumption (at 230V): 23.5W
- Output (at 230V): 54 units on a single power line
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 170x106x83mm
- Weight: 1.5kg



## COSMIC1500DMX

Strobe effect lamp 1500W with DMX control

- Source: 1500W lamp
- Beam angle: 120°
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: strobe rate and brightness, 2channel
- Signal connection: 3p IN/OUT
- Power connection: 16A Shuko plug
- IP rating: 20
- Dimensions (WxHxD): 453x132x214mm
- Weight: 5.2kg