



DISPLAYCOBTRWDFC

60W track mounted and WDMX FC LED fixture



LIGHT SOURCE

60W
COB RGB LED



BEAM ANGLE

60° - 30°
(15° optional)



CONNECTIVITY

DMX512, WDMX,
track adaptor EUTRAC,
STAFF, GLOBAL, IVELA
compatible)



IP RATING

30

DISPLAYCOBTRWDFC is the track mount version of DISPLAYCOBFC. Featuring elegant white housing and wireless DMX module on-board allowing remote control of the light making it a perfect and innovative solution for installations in commercial spaces, showrooms, museums and churches.

DISPLAYCOBTRWDFC employs 60W COB LED source RGB/FC combined with a special parabolic reflector built in aluminium which develops an extremely bright and homogeneous output and interchangeable lens systems to switch from 60°(incl.) to 30°(incl.) and 15°(opt.)

FEATURES

- Track mounted compact LED PAR with 60W FC COB source and wireless DMX control
- HD dimming and an extensive and even colour palette
- Flexible lens options of 15°, 30° and 60° and functional barn doors

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 60W COB RGB LED
- Luminous flux: 2055lm

OPTICS

- Beam angle: 60°

COLOUR SYSTEM

- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets

CONTROL

- Protocols: DMX512, W-DMX
- DMX channels: 3 / 5 / 8 channel
- W-DMX: included, wireless solution receiver

ELECTRICAL

- Power consumption (at 230V): 75W
- Output (at 230V): 19 units on a single power line

PHYSICAL

- Signal connection: XLR 5p IN/OUT connectors
- Power connection: track adaptor (EUTRAC, STAFF, GLOBAL, IVELA compatible)
- IP rating: 20
- Dimensions (WxHxD): 166x118x290mm
- Weight: 1.85kg



DISPLAYCOBTRWDWW

45W track mounted and WDMX warm white LED fixture



LIGHT SOURCE

45W white COB LED



BEAM ANGLE

60° - 30°
(15° optional)



CONNECTIVITY

DMX512, WDMX,
track adaptor EUTRAC,
STAFF, GLOBAL, IVELA
compatible)



IP RATING

30

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 45W white COB LED
- CT: 3200K
- CRI: >97
- Luminous flux: 1682lm

OPTICS

- Beam angle: 60°

CONTROL

- Protocols: DMX512, W-DMX
- DMX channels: 1 / 2 / 5 channel
- W-DMX: included, wireless solution receiver

ELECTRICAL

- Power consumption (at 230V): 62W
- Output (at 230V): 24 units on a single power line

PHYSICAL

- Signal connection: XLR 5p IN/OUT connectors
- Power connection: track adaptor (EUTRAC, STAFF, GLOBAL, IVELA compatible)
- IP rating: 20
- Dimensions (WxHxD): 166x118x290mm
- Weight: 1.85kg

FEATURES

- Track mounted compact LED PAR with 45W warm white COB source and wireless DMX control
- HD dimming and an extensive and even colour palette
- Flexible lens options of 15°, 30° and 60° and functional barn doors