

MINIRUBY

MINIRUBY is an ultra-compact beam light that harnesses all the power of its Osram Sirius 132W lamp into a tight, bright and sharp 3.5° beam. Its small form factor is designed to allow the users to apply a discharge beam light in tight locations or low ceilings bringing a big punch to a small space.

LIGHT SOURCE
- Source: 132W Osram Sirius HRI
- CT: 9200K
- CRI: 60
- Luminous flux: 5150lm

OPTICS
- Beam angle: 3,5°

COLOUR SYSTEM
- Colour wheel: 9 dichroic filters + open

DYNAMIC EFFECTS
- Circular prism: 8f with bi-directional rotation

CONTROL
- Protocols: DMX512, RDM
- DMX channels: 7 / 9channel

ELECTRICAL
- Power consumption (at 230V): 176W
- Output (at 230V): 12 units on a single power line

PHYSICAL
- Signal connection: Amphenol XLR 3p + 5p IN/OUT connectors
- Power connection: Neutrik powerCON IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 278x387x200mm
- Weight: 7.6kg

LIGHT SOURCE
132W Osram Sirius HRI

BEAM ANGLE
3.5°

CONNECTIVITY
DMX512, RDM

IP RATING
20





