



WIFIUSB (optional) LUMIPARIRCH (included)

BATPAR12UTRI

- Source: 12x3W RGB LEDs
- Luminous flux: 1286lm
- Beam angle: 16°
- Protocols: DMX512
- DMX channels: 3/8channel
- W-DMX: optional, proprietary protocol compatible with WIFIBOX, WDBOX
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 36.5W
- Output (at 230V): 35 units on a single power line
- Battery: 14.8V lithium
- Estimated battery life in full-mode up to: 7h
- Re-charge time: 5h/max
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 261x222x100mm
- Weight: 2.86kg



WIFIUSB (optional) LUMIPARIRCH (included)

BATPAR6UTRI

- Source: 6x3W RGB LEDs
- Luminous flux: 659lm
- Beam angle: 16°
- Protocols: DMX512
- DMX channels: 3/8channel
- W-DMX: optional, proprietary protocol compatible with WIFIBOX, WDBOX
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 23.3W
- Output (at 230V): 50 units on a single power line
- Battery: 14.8V lithium
- Estimated battery life in full-mode up to: 7h
- Re-charge time: 4h/max
- Data: USB port for USB WIFI transmitter (optional)
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 231x179x105mm
- Weight: 1.74kg



LUMIPARIRCH (optional)

SMARTTUBE32

- Source: 32W SMD5050 RGB LED
- Luminous flux: 128.4lm
- Beam angle: 360°
- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 3 / 8 / 48 / 50channel
- Pixel control: pixel2pixel control
- W-DMX: integrated, proprietary protocol compatible with WIFIBOX, WDBOX
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 4.1W
- Battery: 11.1V lithium
- Estimated battery life in full-mode up to: 6h
- Re-charge time: 4h/max
- Power connection: IEC IN/OUT connectors
- IP rating: 20
- Dimensions (WxHxD): 160x1520x160mm
- Weight: 1.3kg

KIT INCLUDES

4 SMARTTUBE32, 1 Multi-Changer, 1 LUMIPARIRCH, 1 Carry Bag





LUMIPARIRCH
(included)

SMARTBATTENQ

- Source: 4x8W RGBW LEDs
- Beam angle: 15°
- Colour mixing: RGBW/FC
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 4 / 6 / 8 / 14channel
- Pixel control: 1 / 2 controllable sections
- W-DMX: integrated, proprietary protocol compatible with WIFIBOX, WDBOX
- IR: infrared sensor controlled by remote
- Battery: 24V lithium
- Estimated battery life in full-mode up to: 8h
- Re-charge time: 5h/max
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 33
- Dimensions (WxHxD): 500x172x82mm
- Weight: 3.5kg



LUMIPARIRCH
(optional)

MOBIBLAST

- Source: 3x10W RGBW LEDs
- Beam angle: 10°
- Colour mixing: RGBW/FC
- Protocols: DMX512
- DMX channels: 4/9/16channel
- W-DMX: integrated, proprietary protocol compatible with WIFIBOX, WDBOX
- IR: infrared sensor controlled by remote
- Battery: 14.8V lithium
- Estimated battery life in full-mode up to: 8h
- Re-charge time: 4.5h/max
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 44
- Dimensions (WxHxD): 273x211.5x80mm
- Weight: 3kg



LUMIPARIRCH
(included)

TRUSSPOD3BAT

- Source: 3x3W RGB LEDs
- Beam angle: 16°
- Colour mixing: RGB/FC
- Colour wheel: virtual colour wheel with presets
- Sound mode: music activation through internal microphone and sensitivity control
- Protocols: DMX512
- DMX channels: 3/8 channel
- IR: infrared sensor controlled by remote
- Power consumption (at 230V): 12W
- Battery: 11.1V lithium
- Estimated battery life in full-mode up to: 7.5h
- Re-charge time: 4h/max
- Signal connection: XLR 3p IN/OUT connectors
- Power connection: IEC IN/OUT connectors
- IP rating: 30
- Dimensions (WxHxD): 121x135x108mm
- Weight: 1.29kg