



TABLEDC

Revolutionary full colour event battery table lamp



LIGHT SOURCE

6x3W + 6x1W RGB +
neutral white



BEAM ANGLE

360° designed to
light up standard
160/180cm
ceremony tables



CONNECTIVITY

W-DMX



IP RATING

30

TABLED is an ingenious product which offers beautiful table lighting for events whilst keeping the atmosphere of the room. Based on a stunning aesthetic design, it is not only a stylish centerpiece but fast to deploy and easy to use. With local control and wireless DMX, it can either act as a standalone table light or be part of a spectacular event lighting package.

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 6x3 W + 6x1W RGB + neutral white
- CT: NW 4000K
- CRI: 80

OPTICS

- Beam angle: 360° designed to light up standard 160/180cm ceremony tables

CONTROL

- Protocols: W-DMX
- DMX channels: 4 / 7 / 10channel
- W-DMX: included, wireless solution receiver
- IR: infrared sensor controlled by remote

ELECTRONICS

- Dimmer: linear 0~100% electronic dimmer
- Dimmer curves: 4 different dimming curves available
- Strobe / shutter: 0~30 Hz, electronic

ELECTRICAL

- Power consumption (at 230V): 8.8W

BATTERY

- Battery: 2.20 Ah - 14.8V lithium
- Estimated battery life in colour change mode up to: 14,5h
- Estimated battery life in single colour mode up to: R - 19h, G - 17.5h, B - 17.5h, W - 17.5h
- Estimated battery life in full-mode up to: 9h
- Re-charge connection: power cable fast-charge in pelican case
- Re-charge time: 4h/max

PHYSICAL

- Data connection: W-DMX OEM TRX
- IP rating: 30
- Dimensions (WxHxD): 140x307x220mm
- Weight: 1.18kg



TABLEDW

Revolutionary tunable white event battery table lamp



LIGHT SOURCE

6x1 W + 6x1W
WW+CW LED



BEAM ANGLE

360° designed to
light up standard
160/180cm
ceremony tables



CONNECTIVITY

IR infrared sensor
controlled by remote
(included in the pack, not
included in single unit)



IP RATING

30

TABLED is an ingenious product which offers beautiful table lighting for events whilst keeping with the atmosphere in the room. Based on a stunning aesthetic design, it is not only a stylish centerpiece but fast to deploy and easy to use. With local control it can either act as a standalone table light or part of a spectacular event lighting package.

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 6x1 W + 6x1W warm white + cold white LEDs
- CT: 3200-5600K
- CRI: 80

OPTICS

- Beam angle: 360° designed to light up standard 160/180cm ceremony tables

COLOUR SYSTEM

- Colour mixing: tunable white

CONTROL

- IR: infrared sensor controlled by remote (included in the pack, not included in single unit)

ELECTRONICS

- Dimmer: linear 0~100% electronic dimmer
- Strobe / shutter: 0~30 Hz, electronic

ELECTRICAL

- Power consumption (at 230V): 9W

BATTERY

- Battery: 2200 mAh - 14.8V lithium
- Estimated battery life in single colour mode up to: W - 14h, A - 14.5h
- Estimated battery life in full-mode up to: 8h
- Re-charge connection: Power supply
- Re-charge time: 4h/max

PHYSICAL

- Data connection: W-DMX OEM TRX
- IP rating: 30
- Dimensions (WxHxD): 140x307x220mm
- Weight: 1.16kg