



SOLAR21

21 X 10W IP65 full colour wash light



LIGHT SOURCE

21x10W
RGBW LEDs



BEAM ANGLE

25°



CONNECTIVITY

DMX512



IP RATING

65 for outdoor events

SOLAR21 is a powerful IP65 LED wash light designed to make buildings and outdoor structures really stand out. Ideal for corporate events, festivals and outdoor stage washes the SOLAR family packs a big punch.

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 21x10W RGBW LEDs
- Luminous flux: 6032lm
- Lux: 4072lux @3m full

OPTICS

- Beam angle: 25°
- Lens diameter: 45mm

COLOUR SYSTEM

- Colour mixing: RGBW/FC
- CTC: CTC control through independent DMX channel
- Colour wheel: virtual colour wheel with presets

CONTROL

- Protocols: DMX512
- DMX channels: 4 / 6 / 11channel

ELECTRONICS

- Dimmer: linear 0~100% electronic dimmer
- Dimmer curves: 4 different dimming curves available
- Strobe / shutter: 1-30 Hz, electronic
- Selectable PWM: 600~25K Hz

ELECTRICAL

- Power consumption (at 230V): 176.6W
- Output (at 230V): 21 units on a single power line

PHYSICAL

- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Power connection: Seetronic powerKon waterproof IN/OUT connectors
- IP rating: 65 for outdoor installations
- Dimensions (WxHxD): 494x349.5x98.5mm
- Weight: 8.5kg



SOLAR

36 X 8W IP65 full colour wash light with WDMX



LIGHT SOURCE

36x8W
RGBW LEDs



BEAM ANGLE

25°



CONNECTIVITY

DMX512, W-DMX



IP RATING

65 for outdoor events

SOLAR is a powerful IP65 LED wash light designed to make buildings and outdoor structures really stand out. Ideal for corporate events, festivals and outdoor stage washes, the SOLAR family packs a big punch.

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

- Source: 36x8W RGBW LED
- Luminous flux: 9678lm
- Lux: (25°) 5300lux @3m full

OPTICS

- Beam angle: 25°
- Lens diameter: 38mm
- Additional optics: 45°(optional)

COLOUR SYSTEM

- Colour mixing: RGBW/FC
- Colour wheel: virtual colour wheel with presets

CONTROL

- Protocols: DMX512, W-DMX
- DMX channels: 4 / 6 / 10channel
- W-DMX: included, wireless solution receiver

ELECTRONICS

- Dimmer: linear 0~100% electronic dimmer
- Dimmer curves: 5 different dimming curves available
- Strobe / shutter: 1-25 Hz, electronic

ELECTRICAL

- Power consumption (at 230V): 245W
- Output (at 230V): 6 units on a single power line

PHYSICAL

- Adaptors: XLR and 16A adaptors included
- Signal connection: moulded IP signal IN/OUT connectors
- Data connection: W-DMX OEM TRX
- Power connection: moulded IP power IN/OUT connectors
- IP rating: 65 for outdoor installations
- Dimensions (WxHxD): 587x303x212mm
- Weight: 14.5kg