

DS40TC

Micro speaker with a closed rear cap. Ideal for high-fidelity sound reproduction designed for ceiling mounting.

LOUDSPEAKERS
- System type: closed enclosure ceiling speaker

COMPONENTS
- Full range: 4"

FEATURES
- AES/program power: 3/6W
- Input 100 V: 1.5/3W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 90dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 160÷20.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: terminal with wire

PHYSICAL
- Weight: 0.36kg



DS62T

Ceiling speaker for recessed mounting, ideal for vocal announcements and reproduction of background music in spaces with low ceilings.

LOUDSPEAKERS
- System type: ceiling speaker

COMPONENTS
- Full range: 2.5"

FEATURES
- AES/program power: 3/6W
- Input 100 V: 1.5/3W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 91dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 160÷20.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: screw terminal

PHYSICAL
- Weight: 0.43kg



DS46T

Ceiling speaker for recessed mounting, ideal for vocal announcements and reproduction of background music.

LOUDSPEAKERS
- System type: ceiling speaker

COMPONENTS
- Low frequency: 6"
- High frequency: 1"

FEATURES
- AES/program power: 20/40W
- Input 100 V: 10/20W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 92dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 90÷18.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: terminal with wire

PHYSICAL
- Weight: 1.70kg



DS45T

Ceiling speaker for recessed mounting, ideal for vocal announcements and reproduction of background music.

LOUDSPEAKERS
- System type: ceiling speaker

COMPONENTS
- Low frequency: 5"
- High frequency: 1"

FEATURES
- AES/program power: 10/20W
- Input 100 V: 5/10W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 91dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 100÷16.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: terminal with wire

PHYSICAL
- Weight: 1.24kg



DS67T

Ceiling speaker for recessed mounting, ideal for vocal announcements and reproduction of background music.

LOUDSPEAKERS
- System type: ceiling speaker

COMPONENTS
- Low frequency: 6.5"
- High frequency: 1"

FEATURES
- AES/program power: 10/20W
- Input 100 V: 2.5/5/10W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 93dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 60÷20.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: terminal with wire

PHYSICAL
- Weight: 1.42kg



DS66T

Built-in ceiling loudspeaker, ideal for announcements and background music reproduction.

LOUDSPEAKERS
- System type: ceiling speaker

COMPONENTS
- Full range: 6"

FEATURES
- AES/program power: 6/12W
- Input 100 V: 3/6W

ACOUSTICAL SPECIFICATIONS
- Sensitivity: 91dB @1W/1m (free field)
- Constant voltage: 70/100 V
- Frequency response: 100÷13.000Hz (±3dB)

INPUT/OUTPUT CONNECTORS
- Input signal: terminal with wire

PHYSICAL
- Weight: 0.72kg