9282PWL1FV

400A power lock cable mount socket, single pole, SOURCE, brown

9282PWL2FV

400A power lock cable mount socket, single pole, SOURCE, black

9282PWL3FV

400A powerlock cable-mount socket, single pole, SOURCE, grey

9282PWNTFV

400A power lock cable mount socket, single pole, SOURCE, blue

9282PWGDFV

400A power lock cable mount socket, single pole, SOURCE, green

9282PWL1FP

400A power lock panel mount socket, single pole, SOURCE, brown

9282PWL2FP

400A power lock panel mount socket, single pole, SOURCE, black

9282PWL3FP

400A powerlock panel-mount socket, single pole, SOURCE, grey

9282PWNTFP

400A power lock panel mount socket, single pole, SOURCE, blue

9282PWGDFP

400A power lock panel mount socket, single pole, SOURCE, green

9282PWL1MV

400A power lock cable mount plug, single pole, DRAIN, brown

9282PWL2MV

400A power lock cable mount plug, single pole, DRAIN, black

9282PWL3MV

400A powerlock cable-mount plug, single pole, DRAIN, grey

9282PWNTMV

400A power lock cable mount plug, single pole, DRAIN, blue

9282PWGDMV

400A power lock cable mount plug, single pole, DRAIN, green



9282PWL1MP

400A power lock panel mount plug, single pole, DRAIN, brown

9282PWL2MP

400A power lock panel mount plug, single pole, DRAIN, black

9282PWL3MP

400A powerlock panel-mount plug, single pole, DRAIN, grey

9282PWNTMP

400A power lock panel mount plug, single pole, DRAIN, blue

9282PWGDMP

400A power lock panel mount socket, single pole, DRAIN, green

Technical Data

Max current rating	400A
Max rated voltage to ground	2Kv AC / 3Kv DC
Min flashover	9.5Kv AC/ DC (peak)
Insulating resolution	> 5MOhm @ 500 VDC
Working temp.	-30°C / +125°C
Set screw	120 mm^2
Fire reaction	Flame-retardant
IP rating	up to IP67 (correct coupling)
Electric shock protection	IP2X