

NEW

SOLAR27Q

27 X 10W high brightness indoor/outdoor compact wash light

SOLAR27Q is a compact fan-free outdoor wash light featuring an outstanding brightness of 10,832 lumens. Equipped with 27x10W RGBW full colour LEDs, delivering superior colour mixing. Featuring a slim size as well as the multiple interchangeable optics through magnets, including asymmetrical filters which, all together, make the SOLAR27Q an incredibly flexible device for indoor use and outdoor. Whilst highly-powerful, the SOLAR27Q also benefits from being silent.

FEATURES

- 27x10W RGBW full colour LED, delivering 10'832 lumens
- Compact form factor and fan-free
- Wireless DMX on-board

TECHNICAL SPECIFICATIONS

LIGHT SOURCE

Source: 27x10W CREE RGBW

CT: 5960KCRI: 71,8

Luminous flux: @FULL 10832 lm - With included filter 6987lm

Lux: @FULL (25°) 6133 lux - With included filter 1027lux @3m full

 Other: Magnetic filter included to achieve 45° (60° filter), barn door not included

OPTICS

■ Beam angle: 25° - With included filter 45°

Lens diameter: 36mm

Lens type: honeycomb gapless plano-convex optics

Additional optics: 10° / 15° / 45° / 40° filter / 10X60° filter / 30X60° filter

COLOUR SYSTEM

Colour mixing: RGBW/FC

CTC: CTC control through independent DMX channel

Colour wheel: virtual colour wheel with presets

BODY

■ Tilt angle: +/- 90° manual



Protocols: DMX512, RDM, W-DMX

DMX channels: 5 / 7 / 10 / 13 / 17 channel

Pixel control: 3 horizontal individually select and control sections

W-DMX: included, wireless solution receiver

ELECTRONICS

■ Dimmer: linear 0~100% electronic dimmer

• Dimmer curves: different dimming curves available

Selectable PWM: 600~25K Hz

ELECTRICAL

• Power consumption (at 230V): 268W

Output (at 230V): 9 units on a single power line

PHYSICAL

Signal connection: Seetronic XLR 5p IN/OUT connectors

Data connection: W-DMX OEM TRX

Power connection: Seetronic powerKon waterproof IN/OUT connectors

• IP rating: 65 for outdoor installations

Dimensions (WxHxD): 454x153x268.5mm

Weight: 9kg



LIGHT SOURCE

27x10W CREE RGBW



BEAM ANGLE

25° - with included filter 45°



CONNECTIVITY

DMX512, RDM, W-DMX



IP RATING

65 for outdoor events



