



**NEW**

## SOLAR48Q

48 X 10W high brightness indoor/outdoor compact wash light

SOLAR48Q is a compact fan-free outdoor wash light featuring an outstanding brightness of 22.760 lumens. Equipped with 48 x 10W RGBW full-colour LEDs all delivering superior colour mixing. Featuring a slimline styling, multiple interchangeable optics through magnets, asymmetrical filters which combined, make the SOLAR48Q an incredibly flexible device for indoor and outdoor use. Whilst highly-powerful, the SOLAR48Q is also completely silent.

### FEATURES

- 48x10W RGBW full colour LED delivering 22.760 lumens
- Compact form factor and fan-free
- Wireless DMX onboard

## TECHNICAL SPECIFICATIONS

### LIGHT SOURCE

- Source: 48x10W RGBW/FC LEDs
- Luminous flux: 22760lm
- Lux: (25°) 14900lux @3m full

### OPTICS

- Beam angle: 25° - With included filter 45°
- Additional optics: 10° / 15° / 45° / 40° filter / 10X60° filter / 30X60° filter
- Other: Magnetic filter included to achieve 45° (60° filter), barn door not included

### COLOUR SYSTEM

- Colour mixing: RGBW/FC
- CTC: CTC control through independent DMX channel
- Colour wheel: virtual colour wheel with presets

### DYNAMIC EFFECTS

- FX generator: section effect with 4 horizontal individually select and control sections

### BODY

- Tilt angle: 0-150° manual

### CONTROL

- Protocols: DMX512, RDM, W-DMX

- DMX channels: 5 / 7 / 10 / 17 / 22channel
- W-DMX: included, wireless solution receiver

### ELECTRONICS

- Dimmer: linear 0~100% electronic dimmer
- Dimmer curves: 4 different dimming curves available
- Strobe / shutter: 1 - 30 Hz, electronic
- Selectable PWM: 600~25K Hz

### ELECTRICAL

- Power consumption (at 230V): 521W
- Output (at 230V): 6 units on a single power line

### PHYSICAL

- Signal connection: Seetronic XLR 5p IN/OUT connectors
- Data connection: W-DMX receiver
- Power connection: Seetronic powerCON waterproof IN/OUT connectors
- IP rating: 65 for temporary outdoor application, not for fixed installation
- Dimensions (WxHxD): 563x93x314mm
- Weight: 15.5kg



**LIGHT SOURCE**  
48x10W CREE RGBW



**BEAM ANGLE**  
25° - With included filter 45°



**CONNECTIVITY**  
DMX512, RDM, W-DMX



**IP RATING**  
65 for temporary outdoor application, not for fixed installation